

SSO SNOWMOBILE 2-CYCLE OIL

>>Description

SSO is a 100% synthetic based oil formulated to reduce smoke emissions and provide uncompromised performance under the most severe conditions. Offers "Super Cold Flow" technology and protects piston crowns, cylinder heads, spark plugs, power valves and exhaust ports from harmful carbon deposits. SSO maintains higher compression and improves power output and throttle response. Also provides the highest degree of anti-friction and anti-wear while protecting against rust and oxidation.

>>Features

- >100% synthetic formula
- >The most advanced smokeless technology
- >Improves power efficiency and throttle response
- >Provides superior detergency for clean, deposit free operation
- >Protects under the most severe loads and temperatures
- >Formulated for power valve engines

>>Application

For use in air cooled or liquid cooled snowmobile 2-cycle engines commonly found in Arctic Cat®, Polaris®, Ski-Doo®, Yamaha® and other snowmobile 2-cycle applications. Highly recommended for all types of snowmobile racing.

Exceeds all manufacturer warranty requirements.

Exceeds: JASO-FC / ISO-L-EGD / API-TC

>>Typical/Test Data

Description	SSO
Viscosity @ 100°C	6.8
Viscosity @ 40°C	41.33
Pour Point °C	-50
Flash Point °C	70
Appearance	CL-Purple

>>Directions

Formulated for injector or premix applications. Use at full strength in injector systems. For best performance in premix applications, SSO is recommended at ratios of 32:1 to 40:1.

>>Package Sizes / P/N

Description:	SSO
1 Liter (1.056 US QT)	S960066CE
Case 12 Liters	S960066C
1 Gallon Jug	S960066FE
Case 6 Gallons	S960066F
5 Gallon Pails	S960066E
55 Gallon Drum	S960066B

