

V-SERIES "ST" MOTOR OIL

SAE: 20W/50, 50 & 60

>>Description

V-Series Motor Oils are formulated using highly refined petroleum base stocks and Torco's race proven MPZ® additive providing better cooling, cleaning, ring seal, deposit control and anti-wear protection. Maintains viscosity and provides thermal stability under high temperature environments. V-Series is specifically formulated for Harley® and custom v-twin engines.

>>Features

- >Premium grade petroleum formula
- >MPZ frictional loss technology
- >Prevents oil breakdown at high temperatures
- >Provides superior ring seal
- >Excellent wear protection
- >Extends piston and valvetrain life

>>Application

SAE 20W/50 - For use in late model Evolution® Harley®, S&S® and other high performance v-twin engines

SAE 50 - For use in early model pre- Evolution Harley and other high performance v-twin. For use in temperatures above 60°F (15°C)

SAE 60 - For use in early model pre-Evolution® Harley® and other high performance v-twin engines where higher engine temperatures are present. For use in temperatures above 80°F (30°C)

Exceeds all manufacturer warranty requirements.

Exceeds API SG / JASO-MA

>>Typical/Test Data

SAE Grade	20W/50	50	60
Viscosity @ 100°C	21.3	21.5	26
Viscosity @ 40°C	189	204	286
Pour Point °C	-20	-15	-12
Flash Point °C	229	235	243
Appearance	Amber	Amber	Amber

>>Directions

Follow manufacturer's fill level requirements.

Compatible with other petroleum and synthetic lubricants.

>>Package Sizes / P/N

SAE Grade:	20W/50	50	60
1 Liter (1.056 US QT)	T632050CE	T630050CE	T630060CE
Case 12 Liters	T632050C	T630050C	T630060C
1 Gal Jug	T632050FE	N/A	N/A
Case 6 Gallons	T632050F	N/A	N/A
55 Gallon Drum	T632050B	T630050B	T630060B

